

Axis product selection result



AXIS M3113-R



AXIS M3113-VE



AXIS M3203-V



AXIS P3301-V



AXIS P3343-V 6mm

Camera					
Image sensor	CMOS	CMOS	CMOS	CMOS	CMOS
Image sensor size	1/4"	1/4"	1/4"	1/4"	1/4"
Megapixel sensor					
Sensor size in megapixel					
Progressive scan	✓	✓	✓	✓	✓
Wide dynamic range	✓	✓		✓	✓
Min illumination/ light sensitivity (Color)	1 lux	1 lux	0.9 lux	1 lux	0.2 lux
Min illumination/ light sensitivity (B/W)					0.04 lux
Video					
Day and Night functionality					✓
Max video resolution	800x600	800x600	800x600	640x480	800x600
Max frames per second	30	30	30	30	30
Lens					
Focal length	2.9 mm	2.9 mm	2.8 - 10 mm	2.8 - 10 mm	2.5 - 6 mm
Varifocal			✓	✓	✓
Aperture	2.0	2.0	1.7	1.3	1.2
Horizontal field of view	66	66	66 - 18	72 - 23	72 - 34
PTZ					
Mech. Pan/Tilt					
Digital Pan/Tilt	✓	✓	✓		✓*
Pan range					
Tilt range					
Auto patrol	✓	✓	✓		✓
Optical zoom					
Digital zoom	✓	✓	✓		✓
Compression					
Motion JPEG	✓	✓	✓	✓	✓
H.264	✓	✓	✓	✓	✓
HDTV resolution					
Audio					
Audio support				✓	✓
Two-way audio				✓	✓
Full duplex audio				✓	✓
Built-in microphone				✓	✓
Built-in speaker					
System Integration					
Video motion detection	✓	✓	✓	✓	✓

Audio detection				✓	✓
Active tampering	✓	✓	✓	✓	✓
Alarm inputs/outputs	0/0	0/0	0/0	1/1	1/1
AVHS	✓	✓	✓	✓	✓
Network					
Power over Ethernet	✓	✓	✓	✓	✓
PoE class	1	1	2	2	2
Security					
Multi-level password	✓	✓	✓	✓	✓
HTTPS encryption	✓	✓	✓	✓	✓
IP address filtering	✓	✓	✓	✓	✓
IEEE 802.1X		✓		✓	✓
General					
Slot for memory card					✓
Operational temperature °C	-25 to 50	-20 to 50	0 to 50	0 to 50	0 to 50
Vandal resistant	✓	✓	✓	✓	✓
IP rating	IP66, IP67	IP66, IP67	IP30	IP30	IP30