

Axis product selection result



AXIS P3367-VE



AXIS P3364-VE 6mm



AXIS P3354 6mm



AXIS P3346-VE



AXIS P3344-VE 6mm

Camera					
Image sensor	CMOS	CMOS	CMOS	CMOS	CMOS
Image sensor size	1/3.2"	1/3"	1/3"	1/3"	1/4"
Megapixel sensor	✓	✓	✓	✓	✓
Sensor size in megapixel	5	1	1	3	1
Progressive scan	✓	✓	✓	✓	✓
Wide dynamic range	✓	✓	✓	✓	✓
Min illumination/ light sensitivity (Color)	0.2 lux	0.1 lux	0.1 lux	0.5 lux	0.3 lux
Min illumination/ light sensitivity (B/W)	0.04 lux	0.02 lux	0.02 lux	0.08 lux	0.05 lux
Video					
Day and Night functionality	✓	✓	✓	✓	✓
Max video resolution	2592x1944	1280x960	1280x960	2048x1536	1280x800
Max frames per second	30*	30	30	30*	30
Lens					
Focal length	3 - 9 mm	2.5 - 6 mm	2.5 - 6 mm	3 - 9 mm	2.5 - 6 mm
Varifocal	✓	✓	✓	✓	✓
Aperture	1.2	1.2	1.2	1.2	1.4
Horizontal field of view	84 - 30	105 - 49	105 - 49	84 - 30	87 - 40
Lens mount					
Lens changeable					
PTZ					
Mech. Pan/Tilt					
Digital Pan/Tilt	✓*	✓*	✓*	✓*	✓*
Pan range					
Tilt range					
Guard tour	✓	✓	✓	✓	✓
Optical zoom					
Digital zoom	✓	✓	✓	✓	✓
Compression					
Motion JPEG	✓	✓	✓	✓	✓
MPEG-4					
H.264	✓	✓	✓	✓	✓
HDTV resolution	1080p	720p	720p	1080p	720p
Audio					
Audio support	✓	✓		✓	✓
Two-way audio	✓	✓		✓	✓
Full duplex audio	✓	✓		✓	✓
Built-in microphone					

Built-in speaker					
System Integration					
Video motion detection	✓	✓	✓	✓	✓
Audio detection	✓	✓		✓	✓
Active tampering	✓	✓	✓	✓	✓
Alarm inputs/outputs	1/1	1/1	1/1	1/1	1/1
Serial connectors					
AVHS	✓	✓	✓	✓	✓
Network					
QoS	✓	✓	✓	✓	✓
IPv6	✓	✓	✓	✓	✓
Power over Ethernet	✓	✓	✓	✓	✓
PoE class	3	3	2	3	3
Wireless					
Security					
Multi-level password	✓	✓	✓	✓	✓
HTTPS encryption	✓	✓	✓	✓	✓
IP address filtering	✓	✓	✓	✓	✓
IEEE 802.1X	✓	✓	✓	✓	✓
General					
Slot for memory card	✓	✓	✓	✓	✓
Operational temperature °C	-40 to 55	-40 to 55	0 to 50	-40 to 55	-40 to 55
Vandal resistant	✓	✓		✓	✓
IP rating	IP66	IP66		IP66	IP66
Comments	* 30 in 2MP and HDTV 1080p, 20 in 3MP, 12 in 5 MB			* 30 in 2MP and HDTV 1080p, 20 in 3MP mode	